Price Example

Prefab houses

Construction Space: 160 SQM

Terrace: 25 SQM

Width 12M Depth 9.6M

Distribution of the House: 2 Floors.

Ground Floor: Entry Hall, Foyer, Living Room, Dining Room, Kitchen, Storage, Bathroom, Toilet,

Master Bedroom, Corridor.

First Floor: 2 Bedrooms, Bathroom.

Specification of the House: Turn Key House Fully Finished with All Equipment.


Attachment 1 Conception Drawings Front Elevation








Floor Plans





Attachment 2 Optional Finish Specifications Dining Room



Kitchen



Living Room



Bedroom



Attachment 3: Technical Standards

Thickness of the Wall and Roof Panel: about 220 mm.

Wood Siding 18mm + Air Space 18mm + Waterproof Membrane + OSB 12mm + Wood Support 140mm + Insulation 180mm + PE Vapor Barrier + OSB 12mm + Gypsum Board 12mm

Materials:

Roof Trusses: SPF dimension lumber, No.2; $38\times89 mm$, $38\times140 mm$, $38\times184 mm$, $38\times234 mm$, $38\times286 mm$

Floor Trusses: SPF dimension lumber, No.2; 38×89mm 234mm; Truss spacing: 406mm; More Vertical Web required

Wall panel: Ext. and Int. Wall stud: SPF No.2; 38×140mm; Height 2740mm; Outside Wall: OSB ~ E1/OSB3:9mm; Internal wall: sheathing OSB excluded.

Stairs: SPF 38×286mm SPF 38×286mm; OSB ~ E1/OSB3:15mm

Structure design standard:

Wind Load: 140KM/hour;
 Snow Load: Ground 0.4Kpa;
 Floor distributed live load: 1800N/M²; Seismic grade:
 Fire Resistance Rating: 1 hour;
 Fire Protection Rating:

Attachment 4: Decoration Material and Equipment List Main Materials



Item	Specification	Supplier	Pictures
Roof Truss	SPF lumber 38mmx89mm	Canada	
Floor Truss(only for the upper floor)	SPF lumber 38mmx89mm SPF 2×4	Canada	
External wall structure	SPF lumber 38mmx235 SPF 2×6	Canada	EX11_B_ B
Internal Wall Structure	SPF lumber 38mmx89mm SPF 2×4	Canada	
Installation Accessories	Connectors nails	China	
Sheathing OSB	OSB 9mm, 12mm,15m (Double OSB for roof, OSB for each side of exterior and interior walls)	Canada	

Metal Connector	Mitek	Australia	
Roof Air Structure	TK board TK	China	
Treated Wood	ACQ treated wood ACQ	Canada	
Waterproof Membrane	DuPont/Guardian Wrap	USA	Tyvek Tyvek Tyvek IA
Insulating Wool	Isover	France	ISOVET

Outside Decoration Materials

Outside Window	Aluminum and wooden	China	株成党後級関連共務 JFC340条列 - 1773年 -
----------------	---------------------	-------	---

Entrance Door	Security Door	China	
Roof Clay Tile Tiles	Steel	China	
Waterproof Material	SBS	China	
Rain-carrying System	Metal System	USA	
Outside Wall Siding	Wood & Cement	China	

Inside Decoration Materials



Inside PVC Door	Complex Wood Door	China	
Door Lock	Cogent Standard	China	
Drywall (For Wall & Ceiling)	Lafarge	France	
Real Wood Floor	Oak Parquet Wood Floor	China	
Tile for wall and floor	For Bathroom & Kitchen	China	
Venting System for Bathroom	TCL	China	

Illuming light	TCL	China	
Electricity and Pluming System	Era	China	
Garage Door	Twin	Germany	
Stairs	BBG	China	
Wardrobe	O'SOFT	China	



Kitchen

Wood Closet Brand : O'soft

Style : Natural Countryside



Smoke Extractor Brand : O'soft

Cooker Brand: O'soft Style: BT-680B



Steel Sink Brand: O'soft



Basin Faucet Brand: O'soft



Toilet



Bathtub













