

School Bus



Size

9980×2430×3000 (3150 With A/C)

Length/Width/Height (mm)

Interior height (mm) 1900

Engine

WP5.200 Engine model

WEICHAI WP5.200 diesel engine (Euro 3) BOSCH

Engine type Front mounted, 4 cylinders in-line, 4 stroke, turbo-charged, water cooled,

BOSCH high pressure common rail

147/2300 (200PS)

Max.power/rotating speed (kw/r/min)

735/1200-1700

Max. torque/rotating speed (N.m/r/min)

Performance

Top speed (km/h) ≤ 80

(mm) wheel base (mm) 5700

(mm)

Front overhang / Rear overhang (mm) 1120/3160

Approach angle/ departure angle 16/10

wheel tread (F/R) 2074/1800

Service Cost (Mills - Mills -	V21-24-12-14-02-16	
Fuel tank volume(L)	220	
(L/100km) Fuel consumption	20	
Curb weight(kg)	11500/8730	
Basic Specification		
Clutch		Single, diaphragm type, clutch booster
Transmission		5
		5 forward gears, soft axle distant control
Rear axle		Integral axle housing, single reduction final drive
Front axle		Ends fist, I section
Suspension system		11/12, Leaf spring, F/R 11/12
Steering system		
, , , , , , , , , , , , , , , , , , , ,		Power steering
		WABCO
Braking system		ABS+
blaking system		Brake model: Front disc rear drum brake, dual-circuit air brake, energy storage
		spring parking brake, drier, WABCO ABS+ automatic adjusting arm
Tire		9R22.5 With one spare tire
Functional Specificatio	n	
		SS400 350mm,
		The body of bus is welded by SS400 rectangular steel tube. Monocoque
Body type		structure body, side panels are stretched high-quality galvanized panels. The
		bottom of the chassis is specially treated with anti-corrosion glue. The ground
		clearance of step is 350mm,
Interior trim		

	Front and rear ceiling are both absorbed molding type, flat floor covered with
	luxury durable antiskid floor vinyl, two piece of safety ceiling hatch
Door and door pump	Electric control pneumatic single outward swing door with one rear emergency
	door.
Luggage compartment	No,
Window	Semi-enclosed pull-push window (upper pull-push, lower enclosed), with side
	curtain (faint yellow)
	35-55+1 2+3
Seat and accessories	35-55+1 seats, 2+3 arrangement, common seat, common seat, safety belts,
	with accommodation rail
A/C system	18KW
700 System	Without. Fan, Roof mounted A/C, 18KW is optional.
Heating system	
	Defroster,
Video and Audio	MP3+
	MP3+radio, vehicle mounted megaphone (inside and outside horn)
Lamp	
	Integral front lamp, front ceiling height lamp, side mark lamp.
Paint	
	Paint exclusively for automobile (yellow color exclusively used in school bus).
Others	E-clock, driver sunshade, manual rearview mirror with blind spot mirror,
	automatic engine compartment fire extinguisher, reverse and inner colorful
	monitor (four cameras), electrical parking arm, warning signals exclusively
	eg 664 55 550 55 FED F

used in school bus, reflector, school bus logo, medicine box , tools, instruction, 8kg fire extinguisher, hub

Price Term	FOB YANTAI: 55000USD/Unit (with A/C)	
Payment terms	30% 70%	
	30% advance payment by T/T, 70% balance by T/T before delivery.	
Validity Quotation	2 Two Months	



