YTK6891B 客车配置及参数表

YTK6891B CONFIGURATION & PARAMETER LIST



外形参数 Size		
总长/总宽/总高 Length/Width/Height (mm)	8940×2420×3280	
内高 Interior height (mm)	1900	
发动机 Engine		
发动机型号 Engine model	玉柴欧排二放柴油机,型号: YC6J210-20(Euro2) YUCHAI diesel engine YC6J210-20(Euro 2)	
发动机型式 Engine type	后置,直列四缸四冲程、增压中冷、水冷 Rear mounted,4 cylinders in-line, 4 stroke, turbo-charged, water cooled,	
最大功率/转速 Max.power/rotating speed (kw/r/min)	155/2500	
最大扭矩/转速 Max. torque/rotating speed (N.m/r/min)	710/1300-1500	
排量 Displacement(L)	6.494	
性能参数 Performance		
底盘型号 Chassis model		
最高车速 Top speed (km/h)	115	
轴距 (mm) Axle distance (mm)	4200	
前悬/后悬 (mm) Front overhang / Rear overhang (mm)	2030/2710	
接近角/离去角(°) Angle of approach / departure (°)	12/9	
轮距(前/后)Wheel track(front/rear)(mm)	1922/1800	
制动距离(时速30KM满载状态下)Brake distance (v=30km/h fully loaded)	<10m	
油箱容量 Fuel tank volume(L)	220	
油耗(L/100km)(限定工况下) Fuel consumption (on certain condition)	≤18	
总质量/整备质量 Gross weight/Curb weight (kg)	11950/8600	

基本配置 Basic Specification	
离合器 Clutch	单片,干式、膜片式、直径 395mm
	Single, dry, diaphragm type, diameter is 395mm,
变速器 Transmission	5 档手动带同步器、型号: QJ805
	Domestic 5 forwards manual with synchronizer, model:QJ805
后桥 Rear axle	单级减速,整体式桥壳 , 速比: 4.33
	Integral axle housing, single reduction final drive, speed
	ratio:4.33
前桥 Front axle	拳端式工字梁结构
	Ends fist, I section
悬架系统 Suspension system	钢板弹簧,前/后 9/8
	Leaf spring F/R 9/8
转向系统 Steering system	整体式动力转向
	Integral power steering
	双管路气制动、干燥器 储能弹簧气室、WABCO ABS 带刹车间隙
	自动调整臂
制动系统 Braking system	Dual circuit air brake, drier, energy storage spring chamber,
	WABCO ABS+ automatic backlash adjustment arm
轮胎 Tire	8.25R20,有备胎 with spare tire
тали тте	0.25N20,丹田加 With Spare the
功能配置 Functional Specification	
	SS400 和 16Mn 矩型钢管焊接成型骨架,全承载车身,汽车专用双
	面镀锌板涨拉蒙皮,全车保温隔热处理,底部防腐处理 ,三级踏步
车身类型 Body type	The body of bus is welded by SS400 and 16Mn rectangular
	steel tube. Monocoque structure body, side panels are
	stretched high-quality galvanized panels. The bottom of the
	chassis is specially treated with anti-corrosion glue. The
	whole bus is heat insulation. Three steps
	空调内饰,带读书灯和空调出风口式双面内行李架,豪华换气扇式安
内饰 Interior trim	全顶窗,电动除霜倒车镜,凹地板铺装地板革
	Air conditioner interior trim, double face interior luggage rack
	with reading lamps and A/C ventilators, luxury air change fan
	type safety ceiling window, electric defroster rearview mirror,
	concaved floor with vinyl
 车门及门泵 Door and door pump	单扇外摆乘客前门
十二次口来 Door and door bump	Single leaf outward swinging passenger door
车窗 Window	全封闭式钢化玻璃(两侧后窗为活式)全车豪华折叠式窗帘,推拉式
	司机窗 (司机窗为无色,其余全为茶色)
	Full-closed hardened glass(rear side windows are
	active),luxury foldable curtain, pull-push driver window (driver
	window is clear and others are brown color)
空调系统 A/C system	非独立顶置空调,主要部件如压缩机等为进口,制冷量 22KW
	Dependent ceiling air conditioner, the main component such
	as compressor are imported, and the refrigerating output is
	22KW
暖风系统 Heating system	除霜器
	Defroster

座椅及附件 Seat and accessories	37+1+1 座 (带导游座椅),2+2 排列,高靠背可调座椅,带网袋、 把手、扶手、侧拉、座号牌、全车安全带
	37+1+1 seats(with tour guide seat), 2+2 high-back adjustable
	seats, with bag, handle, armrest, side pull, seat mark, safety
	belts
视听系统 Video and Audio	硬盘播放器+一台 17 寸液晶显示器
	Hard disk+17" LCD monitor
灯具 Lamp	组合前照灯,前顶示高灯,车身侧标志灯,高位刹车灯
	Integral front lamp, front ceiling height lamp, side mark lamp,
	high-level brake lamp
服务设施 Service equipment	电子钟,发动机仓自动灭火器,8KG灭火器,工具箱,四个安全锤
	E-clock, engine compartment automatic fire distinguisher,
	8KG fire extinguisher, vehicle tools, 4 safety hammers
其他 Others	行车记录仪,倒车监视器
	Driver record, rear view monitor









