

## QUOTATION



**Specification sheet**

Overall Specification	Overall length(mm) 总长	10505	Engine Specification	Engine Model 发动机型号	康明斯 B180 20 Cummins B180 20
	Overall width(mm) 总宽	2500		Engine Type 发动机种类	直列、六缸、四冲程、增压中冷 In line, 6 cylinder, 4stroke Turbocharger and intercooler
	Overall height(mm) 总高	3200		Displacement(L) 排量	5.883
	Wheelbase(mm) 轴距	5000		Max. output kw/rpm 最大功率	134/2250
	Tread(mm) 轮距	2020/1860		Max. torque(N.M/rpm) 最大扭矩	610/1500
	Overhang F/R(mm) 悬挂	2275/3230		Fuel Type 燃油总类	Diesel 柴油
	Approach/Departure Angle (°) 接近角/离去角	8/8			
Performance	Passenger capacity 额定载客人数	66		Max. speed(km/h) 最高车速	80
	Engine Position 发动机位置	前置 Front Mounted		Fuel Tank Capacity(L) 油箱容积	200L
	Curb Weight(kg)	8200		Max. total mass(kg)	13000

Item 项目	Standard Equipment 标配	Optional Equipment 选配
Chassis 车架	Clutch 离合器	单片、干式、膜片弹簧离合器，液压气助力操纵， Single dry plate spring clutch, with hydraulic assistance
	Transmission 变速器	ST-60, 五个前进挡，一个倒挡，手动操纵 ST-60, 5 forward speed and one reverse speed, manual operation
	Rear Axle 后桥	东风德纳 9T 后桥，单级主减，鼓式制动 9T axle , DONGFENG axle, drum brake
	Front Axle 前桥	东风德纳 5.5T 前桥，鼓式制动 5.5T axle, DONGFENG axle, drum brake
	Frame 车架	铆接车架 Riveted Frame
	Suspension 悬挂	多片簧、前 12 后 13, 带前横向稳定杆,筒式减震器 Multi-pieces leaf spring(F12/R13), canister shock absorber, front horizontal stabilizing bar
	Steering System 转向系统	整体式动力转向器 power assisted steering
	Brake System 制动系统	双回路气制动系统和鼓式车轮制动器，储能弹簧式驻车制动器 Dual-circuit pneumatic brake ,F/R drum brake Energy storage spring brake
	Tire 轮胎	11.00R22.5-16PR 轮胎，带备胎 11.00R22.5-16PR Tire, with spare tire
	Wiring 电路系统	24V、单线制、负极搭铁 24V, Single wire, Minus earth
	Starter 启动机	24V、电磁操纵型 24v, Electromagnetism Control type
	Battery/Generator 电池/发电机	6-Q-195, 两只/ 28V、70A 6-Q-195, 2 pieces /28v, 70A
Interior Trimming 内饰	Body Structure 车身结构	半承载式车身，冷弯型钢骨架，侧预应力涨拉蒙皮，玻璃钢前后围 Half load bearing type, Cold-bend type steel framework, Pre-stressed pull skin, fiber glass for F/R surround
	Interior Trimming 内饰	墙板，内顶板为 PVC 胶合板，聚酯发泡顶侧面板，吸塑窗柱，发泡靠肩，驾驶员前卷帘遮阳 PVC wall board, and roof board, Polyester foaming side roof board, absorb plastic window, foaming shoulder rest, driver roller sunvisor
	Door and Door Pump 门和门泵	三级踏步，前单内摆门，中门设置残疾人升降机（中门仅供残疾人用），后单内摆门，后门在后轮后方 3-step entrance, Electro-control pneumatic front and rear passenger door, middle door equipped with <b>disabled lift machine</b> (middle door used only for disabled), rear door located behind rear tire

<b>Windows</b> <b>窗户</b>	上粘接固定玻璃，下推拉式铝框侧窗 top fixing and bottom Sliding side Windows, aluminum frame	
<b>Ventilation fan</b> <b>天窗</b>	换气天窗 2 只 2 pcs ventilation hatch	
<b>Floor</b> <b>地板</b>	彩花纹地板革，踏步平面、立面普通地板革 Plastic board with floor leather, standard floor leather for horizontal, vertical surface of step	
<b>Seat</b> <b>座位</b>	40 个蓝色普通吹塑座椅，2 个折叠座椅，(40+2+1 座)，3+2 排列，中门设置残疾人乘坐区域一个，外加两个折叠座椅，可调式驾驶椅 40 blue blow molding plastic seats, 2 folded leather seat, (40+2+1), 3+2 arrangement, one wheelchair area faced middle door, adjustable driver seat	
<b>A/C System</b> <b>空调系统</b>	28000 大卡空调 Air conditioner 28000kcal/h	
<b>Heating System</b> <b>暖风系统</b>	无	
<b>Handrail and Rings</b> <b>扶手和吊环</b>	彩喷扶手 Colorful spray handrail	
<b>Audio &amp; Visual System</b> <b>视听系统</b>	MP3 车载播放器 Mp3 vehicle player	
<b>Rearview System</b> <b>后视系统</b>	纽曼后视镜 KW28 Newman rear view mirror KW28	
<b>Lamp</b> <b>灯具</b>	组合前大灯, 分体式尾灯, 内顶灯 4 只 Combination headlamp with fog lamp, split type tail-light, 4 independent inner roof lights	
<b>Wiper</b> <b>雨刮</b>	异步全景刮水系统 (带喷水系统) Asynchronous panorama wiper (with water spray)	
<b>Service Facilities</b> <b>服务设施</b>	电子钟, 铝框工具箱, 车内 2KG 灭火器 2 只, 喇叭器和扬声器, 垃圾桶, 驾驶员顶风扇, 前后滚动式 LED 电子路牌 8 个汉字长, 4 个下车按钮 Electron clock, Aluminum frame toolbox, two 2KG Extinguishers, microphone and speakers, plastic garbage can, Roof fan for driver, rolling electronic LED bus stop display, 4 buttons to get off	
<b>Others</b> <b>其他</b>	国产素色漆, 原子灰 Domestic painting, atomic ash	



2+3 seat arrangement



2+2 seat arrangement, with front door, middle door for disabled lift machine and rear door behind rear tire



The disabled lift machine,



Rolling LED to display bus stops, 10 English letters can be displayed at one time.