

# QUOTATION

File No.: HT20151120-CKZ6680HBEV

**Model No.: ADICKZ6680HBEV**



## Specification sheet

Overall Specification	Over length(mm)	6800	Engine Specification	Motor model	010WE
	Over width(mm)	2260		Motor manufacturer	Shanghai Dajun power control co., Ltd (China brand)
	Over height(mm)	2850 (with AC)		Position/fuel type	Rear/electricity
	Interior height (mm)	1950		Motor type	Permanent magnet synchronous motor (water cooling)
	Wheelbase(mm)	5000		Rated power (KW/rpm)	60/1600
	Tread(mm)	1890/1680		Peak power (KW/rpm)	110/3500
	Overhang F/R(mm)	910/1690			
	Approach/Departure Angle (°)	18/11			
Performance Specification	Max. speed(km/h)	69	Rated torque (N.m/rpm)	358/1600	
	Engine Position	Rear Mounted	Peak torque (N.m/rpm)	1000/3500	
			Curb Weight(kg)	4860(With AC)	

	Rated passenger capacity (including driver)	45/10-19	Max. total	8500
			mass(kg)	
Item		Standard Equipment		Optional Equipment
Electricity Power system	Drive system	Motor	010WE Permanent magnet synchronous motor rated voltage: 380V AC	
		Motor controller	N490WSA rated capacity:197KVA , maximum capacity: 490KVA,	
		Power battery	Ternary material lithium battery, nominal voltage:388.8V, nominal capacity: 156.8AH, 2PCS in series connection	
CHASSIS	Front axle	3T front axle,17.5" disc brke		
	Rear axle	5.5T rear axle, drum brake		
	Suspension system	Less piece leaf spring(F3/R3), front and rear horizontal stabilizer bar		
	Steering system	Electric power steering sytem		
	Braking system	Double circuit pneumatic brake system, front disc and rear drum brake system, energy storage spring parking system, WABCO ABS system		
	Tyre	205/75R17.5-14PR tubeless radial tire		
	Spare tyre	One piece		
	Other	Drive motor constant temperature system		
	Accumulator	6-Q-105AH, 2 pcs		
INTROIOR TRIMMING	Body structure	Monocoque		
	Interior trim	Facing material roof board, PP molding side panel ,flax duct		
	Door and door pump	Front single outwards swing aluminum door, inside and outside passenger door emergency switch, passenger door emergency master switch at driver's location, left side emergency exit		
	Window, windscreen	Front cementation windscreen, rear cementation tempered windscreen, window-in-glass side window, driver front roller sunshade		
	Rear view system	BONITO rear view mirror, interior mirror		
	AC system	14000 kcal electric air conditioner		
	Defrosting system	DCS-5-WX electric defroster		
	Audio system	None		
	Wiper	Panoramic wiper (with water spray system)		
	Lamp	Independent headlights, tail lights, LED roof light, door light		

	Seat	Adjustable driver seat(3-point safety belt), plastic seats with soft cushion	
	Handrail and Rings	Plastic handrails, no stationary rings	
	Paint	Domestic polyester paint	
	Others	CAN bus wire, 2 modules with cameras, 18mm PVC floor, quartz sand floor leather, 1 pcs roof escape windows with ventilator, 2pcs 2 kg fire extinguisher, 2 pcs safety hammer, 2pcs automatic fire extinguisher in electromotor house, electric clock, automobile data recorder(with GPS), tool box, loud speaker	

## QUOTATION

BUS MODEL	Unit PRICE (USD) Ex work	Terms of payment	DELIVERY TIME	OFFER VALIDITY
CKZ6680HBEV	<b>65,000.00</b>	T/T or L/C 40% as advance payment.	60 days after advance payment	60 days

PICTURES ONLY FOR REFERENCE:

