

Model 6126 Coach (12m Diesel)



外形参数 Size

总长/总宽/总高Length/Width/Height (mm) 12000*2550*3700

内高 Interior Hight (mm) 2010

发动机 Engine

发动机型号 Engine model 潍柴欧三排放柴油机，型号：WP10.336N

WEICHAI diesel engine WP10.336N (Euro 3)

发动机型式 Engine type

后置，直列六缸四冲程、增压中冷、水冷、BOSCH高压共轨系统

Rear mounted, 6 cylinders in-line, 4 stroke, turbo-charged, water cooled, BOSCH high pressure common rail system

排量 Displacement (L)

9.726

最大功率/转速

247/1900

Max.power/rotating speed (kw/rpm)

最大扭矩/转速

1550/1200-1500

Max. torque/rotating speed (kw/rpm)

性能参数 Performance

底盘型号 Chassis model

ND6120YC30

最高车速 Top speed (km/h)	120
轴距 Axle distance (mm)	6000
前悬/后悬 Front / Rear Overhang (mm)	2750 / 3250
接近角/离去角 Angle of Approach / Departure (°)	8.5/9
轮距（前/后） Wheel Trach (Front / Rear) (mm)	2046 / 1850
制动距离（时速30KM满载状态下）	<10m
Brake Distance (V=30km/h fully loaded)	
油箱容积 Fuel Tank (L)	280
油耗（L/100km）（限定工况下）	≤24
Fuel consumption (on certain condition)	
总质量/整备质量（kg） Curb weight	17000/12700
基本配置 Basic Specification	
离合器 Clutch	单片、干式、从动盘，φ 430mm膜片式
	Single, dry, driven disk, φ430mm, diaphragm
变速器 Transmission	S6-150, 6档手动变速箱带同步器，德国ZF技术
	S6-150, 6 forwards manual, with synchronizer, German ZF technology
后桥 Rear axle	单级减速，整体式桥壳，鼓式制动
	Single reduction final drive, integral axle housing, Drum brake
前桥 Front axle	拳端式工字梁结构，盘式制动 Ends fist, I section, Disk brake
悬架系统 Suspension system	空气悬挂2/4 Air suspension F/R 2/4
转向系统 Steering system	整体式动力转向 Integral power steering
制动系统 Braking system	双管路气制动、干燥器、储能弹簧气室、WABCO ABS 带刹车间隙自动调整臂、电涡流缓速器
	Dual circuit air brake, drier, energy storage spring chamber, WABCO ABS + automatic backlash adjustment arm, electrical wave absorber
轮胎Tire	规格：12R22.5，有备胎 Specification: 12R22.5, with spare tire

功能配置 Functional Specification	
车身类型 Body type	SS400和16Mn矩型钢管焊接成型骨架，全承载车身，汽车专用双面镀锌板涨拉蒙皮，全车保温隔热处理，底部防腐处理，四级踏步
	The body of bus is welded by SS400 and 16Mn rectangular steel tube, Monocoque structure body, side panels are stretched high-quality galvanized panels. The bottom of the chassis is specially treated with anti-corrosion glue. The whole bus is heat insulation, four steps.
内饰 Interior trim	空调内饰，带读书灯和空调出风口式双面内行李架，豪华换气扇式安全顶窗，电动除霜倒车镜，凹地板铺装耐磨地板革
	Air conditioner interior trim, double face interior luggage rack with reading lamps and A/C ventilators, luxury air change fan type safety ceiling window, electric defroster rearview mirror, concaved floor with wear-resisting vinyl.
车门及门泵 Door and door pump	单扇外摆乘客前门 Single leaf outward swinging passenger door
车窗 Window	全封闭式钢化玻璃（两侧后窗为活式），全车豪华折叠式窗帘，推拉式司机窗（司机窗为无色，其余全为茶色）
	Full-closed hardened glass (rear side windows are active), luxury foldable curtain, pull-push driver window (driver window is clear and others are brown color)
空调系统 A/C system	非独立顶置空调，主要部件如压缩机等为进口，制冷量28KW
	Dependent ceiling air conditioner, the main component such as compressor are imported, and the refrigerating output is 28KW
暖风系统 Heating system	除霜器 Defroster
座椅及附件 Seat and accessories	49+1+1 座（带导游座椅），2+2高靠、背可调式航空座椅，带网袋、把手、扶手、侧拉、座号牌、全车安全带
	49+1+1 seats (with tour guide seat), 2+2 airline high-back adjustable seats, with bag, handle, armrest, side pull, seat mark, safety belts
视听系统 Video and Audio	硬盘播放器+ 一台17寸液晶显示器+ 一台15寸液晶显示器 Hard disk player + 17" LCD monitor + 15" LCD monitor
灯具 Lamp	组合前照灯，前顶示高灯，车身侧标志灯，高位刹车灯
	Integral front lamp, front ceiling height lamp, side mark lamp, high-level brake lamp
服务设施 Service equipment	电子钟，发动机仓自动灭火器，8KG灭火器，工具箱，四个安全锤
	E-clock, engine compartment automatic fire distinguisher, 8KG fire extinguisher, vehicle tools, 4 safety hammers
其他 Others	行车记录仪，电磁风扇离合器，集中润滑装置，倒车监视器
	Driver record, electric magnetic radiator clutch, central lubrication assembly, rear view monitor