

## QUOTATION OF CONTAINER STATION







TO:

Date: 2018-6-8

| S.N | Item and description  | Image  | QTY (Set) | Unit price (USD) | Amount (USD) |
|-----|---|--|-----------|------------------|--------------|
| 1   | Container station CT-20<br>1 x 20 Feet ISO container case<br>1 x Storage tank with single wall 6mm 26000 L<br>1 x Loading Pump YTB-50, 500L/M, 2KW, 220V<br>1 x Fuel dispenser with 1 product RT-C112 Diesel 75L/M, EX approved<br>With fire extinguisher, tool box, first aid box        |    | 1         | 17,500           | 17,500       |
| 2   | Container station CT-20<br>1 x 20 Feet ISO container case<br>1 x Storage tank with single wall 6mm 26000 L<br>2 x Loading Pump YTB-50, 500L/M, 2KW, 220V<br>1 x Fuel dispenser with 1 product RT-C222 45L+ 75L/M, EX approved<br>With fire extinguisher, tool box, first aid box          |   | 1         | 21,000           | 21,000       |
| 3   | Container station CT-20<br>1 x 20 Feet ISO container case<br>1 x Storage tank with <b>Double wall</b> 6mm 26000 L<br>1 x Loading Pump YTB-50, 500L/M, 2KW, 220V<br>1 x Fuel dispenser with 1 product RT-C112 Diesel 75L/M, EX approved<br>With fire extinguisher, tool box, first aid box |  | 1         | 21,000           | 21,000       |
| 4   | Container station CT-20<br>1 x 20 Feet ISO container case<br>1 x Storage tank with <b>Double wall</b> 6mm 26000 L<br>2 x Loading Pump YTB-50, 500L/M, 2KW, 220V<br>1 x Fuel dispenser with 1 product RT-C222 45L+ 75L/M, EX approved<br>With fire extinguisher, tool box, first aid box   |  | 1         | 25,000           | 25,000       |
| 5   | Container station CT-40<br>1 x 40 Feet ISO container case<br>1 x Storage tank with single wall 6mm, 68000 L MAX<br>1 x Loading Pump YTB-50, 500L/M, 2KW, 220V<br>1 x Fuel dispenser with 1 product RT-C112 Diesel 75L/M, EX approved<br>With fire extinguisher, tool box, first aid box   |  | 1         | 25,000           | 25,000       |
| 6   | Container station CT-40<br>1 x 40 Feet ISO container case<br>1 x Storage tank with single wall 6mm, 68000 L MAX<br>2 x Loading Pump YTB-50, 500L/M, 2KW, 220V<br>1 x Fuel dispenser with 1 product RT-C222 45L+ 75L/M, EX approved<br>With fire extinguisher, tool box, first aid box     |  | 1         | 29,000           | 29,000       |

|   |  |  |   |        |        |
|---|--|--|---|--------|--------|
| 7 | <p>Container station CT-40<br/> 1 x 40 Feet ISO container case<br/> 1 x Storage tank with Double wall 6mm, 68000 L MAX<br/> 1 x Loading Pump YTB-50, 500L/M, 2KW, 220V<br/> 1 x Fuel dispenser with 1 product RT-C112 Diesel 75L/M, EX approved<br/> With fire extinguisher, tool box, first aid box</p> |  | 1 | 29,500 | 29,500 |
| 8 | <p>Container station CT-40<br/> 1 x 40 Feet ISO container case<br/> 1 x Storage tank with Double wall 6mm, 68000 L MAX<br/> 2 x Loading Pump YTB-50, 500L/M, 2KW, 220V<br/> 1 x Fuel dispenser with 1 product RT-C222 45L+ 75L/M, EX approved<br/> With fire extinguisher, tool box, first aid box</p>   |  | 1 | 35,000 | 35,000 |
|   |  |  |   |        |        |

**Optional**

| S.N | Item and description  | Image   | QTY (Set) | Unit price (USD) | Amount (USD) |
|-----|---|---|-----------|------------------|--------------|
| 1   | Tank Gauging System- Console<br>1 control 2   |    | 1         | 600              |              |
| 2   | Probe<br>Installed inside the tank, and communication with console to send the information of the tank<br>Material: SS316       |   | 2         | 650              |              |
| 3   | Leakage detecting system<br>Power supply: DC36V<br>IP grade: 65<br>Communication: M-bus   |  | 2         | 600              |              |
| 4   | LTMS Management system with APP cell phone management   |  | 1         | 400              |              |
| 5   | IC Card Management system for self-service  |  | 1         | 2,200            |              |
| 6   | Gasoline Generator<br>Engine: 1 cylinder, 4 stroke, air cooled gasoline engine<br>Working capacity: 350 cc<br>Max output: 10 KW |  | 1         | 1,400            |              |

**Terms and conditions**

1. LIFE TIME OF FILLING STATION: 10 Years
2. WARRANTEE: ONE YEAR, WITHIN ONE YEAR, WE WILL OFFER YOU FREE PARTS FOR REPLACEMENT
3. PAINTING COLOR: WHITE, WITH YOUR LOGO
4. COST OF COMMISSIONING SERVICE: 120 USD PER DAY PER PERSON
5. Payment terms: T/T. 50% IN ADVANCE, 50% BALANCE BEFORE SHIPPING
6. Lead time: 50 DAYS AFTER THE RECEIPT OF ADVANCE PAYMENT

| Items  | 20FT                | 40FT                |
|--|---------------------|---------------------|
| Container Type                                   | ISO 20FT            | ISO 40FT            |
| Rear Distribution                                | Yes                 | YES                 |
| Service area Doors                               | Yes                 | YES                 |
| Maritime Corrosion protection                    | Yes                 | YES                 |
|  |                     |                     |
| <b>TANK</b>                                      | MAX 26000L          | MAX68000L           |
| Type   | Rectangular Tank    | Rectangular Tank    |
| Tank Wall  | Single/Double       | Single/Double       |
| Compartment                                      | One / Two           | One / Two           |
| WallThickness                                    | 6mm/6mm Q345R       | 6mm/6mm Q345R       |
| Electrical equipment explosion proof standards   | EX Proofed          | EX Proofed          |
| Standards  | BS799-5:2010        | BS799-5:2010        |
|  |                     |                     |
| Fluid Retaining system                           | Yes                 | Yes                 |
| Man Holes  | 2                   | 2                   |
| Vent   | Yes                 | Yes                 |
| Fluid recuperation system                        | Yes                 | Yes                 |
| Anti-slip grid floor with recuperation container | Yes                 | Yes                 |
| Piping system                                    | Welded steel Tested | Welded steel Tested |
| Filling system                                   | DN50                | DN80                |
| Aspiration DN40 with check valve                 | DN40                | DN40                |
| Vent   | DN50, with filter   | DN50, with filter   |
| Pump   | TYB-60              | TYB-60              |
| Dispenser  | RT-C112 / RT-C222   | RT-C112 / RT-C222   |
| Gage   | Manual /pneumatic   | Manual /pneumatic   |
| Primer   | Zinc                | Zinc                |
| Finition Coat /Paint                             | polyurethane 2 coat | polyurethane 2 coat |
| Electrical box with protections                  | Yes                 | Yes                 |
| Ladder   | Yes                 | Yes                 |
| Fire fighting equipment                          | Yes                 | Yes                 |
| Office with EX LED Light and AC                  | Option,Not included | Option,Not included |
| Canopy   | Option,Not included | Option,Not included |
| GENSET   | Option,Not included | Option,Not included |