

SAM II APC is the latest addition to the Rhino Defence fleet of ingenious solutions. Built monocoque using a Ford F-550 Super duty drive train with upgraded suspension. This unique approach makes SAM II cost effective yet capable to withstand greater threats and to compete with rivals.



GENERAL SPECIFICATION

	ENGINE	
Model	Power Stroke®	^₃ V8 Turbo Diesel
Туре	4 Stroke Diese	
No Of Cylinders	8	
Displacement	6,7L	
Max Power	330Hp @ 200	0 rpm
Max Torque	949 @ 2000 rj	om
Fuel	Diesel Euro 3	
	AXLES	
Front	Rigid Twin-Co	il Monobeam axle
Rear	Rigid axle	
Ratio	17.31:1 averag	
GEOME	TRIC PROPER	TIES
Overall Length		6,116mm ± 15mm
Max Width		2,453 mm ± 15mm
Max Height (over	utility bar)	2,432 mm ± 15mm
Ground Clearance		320 mm ± 10mm
Wheel Base	1	3,576mm ± 10mm
Track Width Front		1,900 mm ± 5mm
Track Width Rear		1,900 mm ± 5mm
Angle Of Approach		46°
Angle Of Departure		41°
T	RANSMISSION	
Model	TorqShift® 6-Spe	eed SelectShift™
Configuration	Atomatic	
ŤΙ	RANSFER CASE	
Model	Integrated to transmission	
Configuration [Direct mount dial shift	
PROTECTION LEVELS		
Ballistic Protection E	EN 1522 FB7	
Mine Protection S	STANAG II	
Transparent Armor E	N 1063 BR7	
	BRAKES	
	Disc Brakes	
Parking Brakes	Cable pull disc	
	STEERING	
	Assisted Rack	
	TRICAL SYSTEM	
Voltage Du	iai 12-volt; 75	50-cca/78-amp-hr

FUEL TANKS 68 gallons (DRW - dual diesel tanks) Protection EN 1522 FB6 MASS Curb Weight 7,900Kg Tare mass (Min) Payload 1,500Kg (Max) GVM 9,400Kg (Max) PERFOMANCE Maximum Speed 120Km/h Grade Ability 50% Side Slope 40% Step Climb 250mm Fording 700mm Range 600Km WHEELS
Fuel Capacity tanks) Protection EN 1522 FB6 MASS Curb Weight 7,900Kg Tare mass (Min) Payload 1,500Kg (Max) GVM 9,400Kg (Max) PERFOMANCE Maximum Speed 120Km/h Grade Ability 50% Side Slope 40% Step Climb 250mm Fording 700mm Range 600Km
Protection MASS Curb Weight 7,900Kg Tare mass (Min) Payload 1,500Kg (Max) GVM 9,400Kg (Max) PERFOMANCE Maximum Speed 120Km/h Grade Ability 50% Side Slope 40% Step Climb 250mm Fording 700mm Range 600Km
Curb Weight 7,900Kg Tare mass (Min) Payload 1,500Kg (Max) GVM 9,400Kg (Max) PERFOMANCE Maximum Speed 120Km/h Grade Ability 50% Side Slope 40% Step Climb 250mm Fording 700mm Range 600Km
Payload 1,500Kg (Max) GVM 9,400Kg (Max) PERFOMANCE Maximum Speed 120Km/h Grade Ability 50% Side Slope 40% Step Climb 250mm Fording 700mm Range 600Km
Payload 1,500Kg (Max) GVM 9,400Kg (Max) PERFOMANCE Maximum Speed 120Km/h Grade Ability 50% Side Slope 40% Step Climb 250mm Fording 700mm Range 600Km
GVM 9,400Kg (Max) PERFOMANCE Maximum Speed 120Km/h Grade Ability 50% Side Slope 40% Step Climb 250mm Fording 700mm Range 600Km
Maximum Speed 120Km/h Grade Ability 50% Side Slope 40% Step Climb 250mm Fording 700mm Range 600Km
Grade Ability 50% Side Slope 40% Step Climb 250mm Fording 700mm Range 600Km
Side Slope 40% Step Climb 250mm Fording 700mm Range 600Km
Step Climb 250mm Fording 700mm Range 600Km
Fording 700mm Range 600Km
Range 600Km
WHEELS
Tires 335/80 R20
Rims Steel Split Rims
Configuration 4 x Driven + 1 Spare
SUSPENSION
Front Upgraded Coil Spring + Gas shocks
Rear Upgraded Leaf Spring + Gas shocks
STANDARD FEATURES
Turret provision
Rear differential lock
Gun ports, 4 each side 1 rear
Rear view camera
Escape hatch
2 x Dry powder fire extinguisher
Extraction Fan
Utility bar
16000 BTU A/C OPTIONAL FEATURES
Electrical winch
24v Alternator system
Communication systems
Scene Lights
Vertical gun racks
Vertical gun racks Jamming systems
Jamming systems
Jamming systems P/A Siren System
Jamming systems P/A Siren System Wig/Wag lights
Jamming systems P/A Siren System Wig/Wag lights STIS tire inflation system

Blast retention seats

without written permission from Rhino Defence. Rhino Defence retains the right to alter or change any product and or publication without prior notice. Note: This document is deemed to be correct on date of publishing. Any information in this document should not be copied, r eproduced or used in any contract or order