

EVERYTHING under u

QUOTATION								
Item No.	IMAGE	CARTON					FOB	
		SIZE /cm	WEIGH T /Kg	/carton	Description	Quantity (pcs)	Unit Price (USD)	
	9100 full face mask	44*41*46.5	8.5		 ✓ Replaceable filter element ✓ GB2890-2009、EN140:1680 ✓ Design of head-mounted adjustable buckle ✓ Large view ✓ Universal interface for multiple filter box selection ✓ Anti-scratch lens coating 	3600	25	
NOTES								

Mode of transport	1. The price is based on FOB Qingdao port and keeps valid for 30 days.
Delivery time	 Delivery is 30 days upon confirmation of purchasing order advance payment, whichever is late.
	If there are custom packages or molds, the delivery time needs to be determined through communication between the two parties.
Payment terms	 Purchase quantity is large, payment method is 50% in advance by TT. Pay the final payment before delivery.
	2. Purchase quantity is small, payment method is 100% in advance by TT.

Product name	9100G full face mask				
Product picture	ASC SIGN OF THE PROPERTY OF TH				
Produc parame	 The leakage rate of the protective cover should not be greater than 0.05%. The binocular vision of the protective cover should not be less than 70%, and the lower visual field should be no less than 35 degrees. The axial tension of the connection between the filter and the protective hood should not be less than 50N. 				

	1 respirator should be made up of filter and mask, or composed of protective hood and filter. The mask should be a full mask.
	2. Filtration device connector adopts threaded interface to meet EN148-1 standard requirements.
Design feature	3. The mask is made of multi-point headband, which is convenient for wearing and adjusting. The headband can be pulled fast and easy to release.
	4、 the mask has a no
	5、se and mouth cover to ensure that the screen is not foggy.
	6. the mask filter device is connected with an exhalation valve piece, which can effectively reduce respiratory resistance.
	1. Silica gel materials used in respirators do not show obvious deformation, damage,
	adhesion, cracking, hardening and other abnormal phenomena after high and low temperature tests.
Product features	2. After the fire-resistant test, all materials that may touch the flame do not appear to continue burning, melting and other phenomena, and do not cause additional harm to the human body.
	3. The surface screen shall be reinforced with silicon coated polycarbonate lenses with excellent impact and scratch resistance.
	4、The mask is closely and comfortably close to the face of the person.
Product configuration	The mask contains instructions for use.



Tai'an hengchang labor protection supplies Co.Ltd is a manufacturer of respiratory protection products with well-equipped testing facilities and strong technical force.

With a wide range, good quality, reasonable prices and stylish designs, our products are extensively used in petroleum, petrochemical, chemical, metallurgical, mining and other industries.

Gas masks and dust masks have CE certification. We can provide you OEM and ODM services.

Our products are widely recognized and trusted by users and can meet continuously changing economic and social needs.

We welcome new and old customers from all walks of life to contact us for future business relationships and mutual success!



















SGS

C€

Cell Phone: +86 15056932072

Email: asl@asl1985.com

Mhatsapp: +86 15056932072

WeChat: 15056932072