

***TRUCK AND BUS TYRES
STEEL AND ALLOY WHEELS***



PATTERN DISPLAY

	Long-Distance Transport + National & Regional Transport 	Mixed Services 	Mine & Construction Site 
STEER/ALL POSITION 	 GM103 GM101 GM102 GM105 GM107  GM108S GM109 GM110 GM111 GM112	 GM106 GM115	 GM302
DRIVER 	 GM201 GM580  GM208 GM209 GM210	 GM202 GM203 NEW GM211  GM212 GM215 GM216 GM217  GM218 NEW NEW	 GM303 GM305  NEW GM306
TRAILER 	 GM301 GM102 GM107 GM109		

TRUCK & BUS TIRE



03

04

TRUCK & BUS TIRE

TRUCK & BUS TIRE

GM101

mixed pattern for steering, outstanding performance, anti-sideslip, low noise, suitable for all kinds of road use and rural areas.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
6.50R16	12	L	5.50F	110 105	670	1060	925	185	750	12
7.00R16	14	L	5.50F	118 114	770	1320	1180	200	775	12
7.50R16LT	14	K	6.00G	122 118	770	1500	1320	215	805	13
8.25R16LT	16	K	6.50H	128 124	770	1800	1600	235	855	14
9.00R20	16	J	7.0	144 142	900	2800	2650	259	1019	15.5
10.00R20	18	J	7.5	149 146	930	3250	3000	278	1054	16
11R22.5	16	J	8.25	146 143	830	3000	2725	279	1054	16
11.00R20	18	J	8.0	152 149	930	3550	3250	293	1085	16.5
12.00R20	20	J	8.5	156 153	900	4000	3650	315	1125	17
12.00R24	20	K	8.5	160 157	900	4500	4125	315	1226	14
12R22.5	18	L	9.00	152 149	930	3550	3250	300	1085	16.5
13R22.5	18	L	9.75	154 151	830	3750	3450	320	1124	16.5
315/80R22.5	20	L	9.00	156 150	850	4000	3350	312	1076	15

TRUCK & BUS TIRE

GM102

High durability, high heat resistance, excellent wear resistance, excellent resistance to eccentric wear, good control stability, excellent horse. Suitable for short and middle distance high-speed buses, trucks, the airport bus, etc. suitable for the front wheel.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
9.5R17.5	18	M	6.75	143 141	875	2725	2575	240	842	13.5
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1054	15
12R22.5	16	M	9.00	150 147	830	3350	3075	300	1085	14.5
12R22.5	18	M	9.00	152 149	930	3550	3250	300	1085	14.5
215/75R17.5	16	J	6.00	135 133	850	2180	2060	211	767	13
235/75R17.5	16	M	6.75	132 129	850	2000	1850	233	797	12.5
255/70R22.5	16	M	7.50	140 137	830	2500	2300	255	930	14.5
275/70R19.5	18	M	8.25	148 145	900	2150	2900	276	958	14.5
295/75R22.5	14	L	9.00	144 141	760	2800	2575	298	1014	15
295/80R22.5	18	M	9.00	152 149	900	3550	3250	298	1044	15
315/80R22.5	20	M	9.00	156 150	850	4000	3350	312	1020	15
315/80R22.5	20	L	9.00	156 150	850	4000	3350	312	1076	15

GM103

STRENGTHENED DESIGN

TRUCK & BUS TIRE

Excellent durability, Good ground grasping capacity, Low heat generation, Suitable for medium and long mileage vehicles running on the paved road with a standard load.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
295/80R22.5	18	M	9.00	152 149	900	3550	3250	298	1044	16
315/80R22.5	20	M	9.00	156 150	850	4000	3350	312	1076	18

TRUCK & BUS TIRE

GM105

Apply to paved and high-speed roads, long-distance vehicles. High-speed stability, strong resistance, super wear resistance, good heat resistance.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
385/65R22.5	20	K	11.75	160	900	4500	—	389	1072	17
425/65R22.5	20	J	12.25	164	830	5000	—	422	1124	18

GM106

TRUCK & BUS TIRE

High-performance mixed pattern, suitable for all kinds of complicated road and all position.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
10.00R20	18	L	7.5	149 146	930	3250	3000	278	1054	16
11.00R20	18	L	8	152 149	930	3550	3250	293	1085	16.5
12.00R20	18	L	8.5	154 151	830	3750	3450	315	1125	17
12.00R20	20	L	8.5	156 153	900	4000	3650	315	1125	17
12.00R24	20	K	8.5	160 157	900	4500	4125	315	1226	17

TRUCK & BUS TIRE

GM107

High speed, high load, lateral spreads, wet resistance, small rolling resistance, Suitable for the front wheel or the all positions.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1054	15
12R22.5	16	M	9.00	150 147	830	3350	3075	300	1085	14
12R22.5	18	M	9.00	152 149	930	3550	3250	300	1085	14
295/75R22.5	14	L	8.25	144 141	760	2800	2575	298	1014	15

TRUCK & BUS TIRE **GM108S**

High speed, high load, lateral spreads, wet resistance, small rolling resistance, Suitable for the front wheel or the all positions.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11R22.5	14	M	8.25	144 142	720	2800	2650	279	1054	17
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1054	17

07

TRUCK & BUS TIRE **GM110**

Apply to good paved road surface with high speed road, long-distance vehicles. High speed driving stability, super wear resistance, low noise, good heat resistance, good drainage, good load capacity.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
9.5R17.5	18	M	6.75	143 141	875	2725	2575	240	842	13.5
215/75R17.5	16	J	6.00	135 133	850	2180	2060	211	767	12.5
235/75R17.5	16	M	6.75	132 129	830	2000	1850	233	797	12.5
255/70R22.5	16	M	7.50	140 137	830	2500	2300	255	930	14.5
265/70R19.5	16	M	7.50	140 138	775	2500	2360	262	867	14.5
265/70R19.5	18	J	7.50	143 141	850	2725	2575	262	867	14.5
275/70R22.5	18	M	8.25	148 145	900	3150	2900	276	958	14.5

08

TRUCK & BUS TIRE **GM109**

High speed .Excellent load.
Excellent sideslip and mud slip resistance.
Suitable for medium and short mileage vehicles running on paved road



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
315/80R22.5	20	M	9.00	156 150	850	4000	3350	312	1076	15

TRUCK & BUS TIRE **GM111**

High wear-resisting performance, loading quantity, anti-stung ability, suitable for dive wheels.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
385/65R22.5	20	K	11.75	160	900	4500	—	389	1072	16.5



GM112

TRUCK & BUS TIRE

Improved formula and structure.
High speed, high load, lateral spreads, wet resistance, small rolling resistance, Suitable for the front wheel or the trailers.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11R22.5	14	M	8.25	144 142	720	2800	2650	279	1054	15
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1054	15
11R24.5	14	M	8.25	146 143	720	3000	2725	279	1104	15
11R24.5	16	M	8.25	149 146	830	3250	3000	279	1104	15
225/70R19.5	14	M	6.75	128 126	760	1800	1700	226	811	13.4
245/70R19.5	16	J	7.5	135 133	830	2180	2060	248	839	12.7
265/70R19.5	16	M	7.5	140 138	775	2500	2360	262	867	14.5
285/75R24.5	14	L	8.25	144 141	760	2800	2575	283	1050	15
295/75R22.5	14	M	9.00	146 143	830	3000	2725	298	1014	15
305/70R19.5	16	M	9.00	148 145	850	3150	2900	305	923	14.5

GM115

TRUCK & BUS TIRE

Long time service life with the special formula, The gutter on the tread can reduce the noise and heat dispersion.
Suitable for all kinds of position on the trucks loading for middle and long distance on the good road.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11.00R20	18	L	8.0	152 149	930	3550	3250	293	1085	16.5
12.00R20	18	L	8.5	154 151	830	3750	3450	315	1125	17
12.00R20	20	L	8.5	156 153	900	4000	3650	315	1125	17
12R22.5	16	M	9.00	150 147	830	3350	3075	300	1085	18
12R22.5	18	M	9.00	152 149	930	3550	3250	300	1085	18
13R22.5	18	L	9.75	154 151	830	3750	3450	320	1124	16.5

GM201

TRUCK & BUS TIRE

High speed, high load, excellent traction, braking, resistance performance, applicable to the drive wheels.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1054	21

GM202

TRUCK & BUS TIRE

High wear-resisting performance, loading quantity, anti-stung ability, suitable for all the road situations.



Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1065	21
12R22.5	18	L	9.00	152 149	930	3550	3250	300	1085	22
265/70R19.5	18	J	7.50	143 141	850	2725	2575	262	8267	20
295/80R22.5	18	M	9.00	152 149	900	3550	3250	298	1050	20
305/70R19.5	16	M	9.00	148 145	850	3150	2900	305	923	20

TRUCK & BUS TIRE

GM203

Extra deep tread depth offer excellent traction
Heavy bead design to support heavy load
Suitable for mining&mountain road

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
12.00R24	20	K	8.50	160 157	900	4500	4125	315	1226	17

TRUCK & BUS TIRE

GM209

High wear-resisting performance, loading quantity, anti-stung ability, suitable for dive wheels.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
315/80R22.5	20	L	9.00	156 150	850	4000	3350	312	1076	20

TRUCK & BUS TIRE

GM208

Ultra drive and brake ability, tearing resistance, cutting resistance, abrasion resistance, good load capacity, mixed road surface and generally topdress, medium and short vehicles use, suitable for driving wheel, drag wheels.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1054	22

TRUCK & BUS TIRE

GM211

High wear-resisting performance, loading quantity, anti-stung ability, suitable for dive wheels.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11R24.5	14	M	8.25	146 143	720	3000	2725	279	1116	22
11R24.5	16	M	8.25	149 146	830	3250	3000	279	1116	22

TRUCK & BUS TIRE

GM212

Ultra drive and brake ability, tearing resistance, cutting resistance, abrasion resistance, good load capacity, mixed road surface and generally topdress, medium and short vehicles use, suitable for driving wheel, drag wheels.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
9.5R17.5	18	M	6.75	143 141	875	2725	2575	240	842	14.5
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1065	22
215/75R17.5	16	J	6.00	135 133	850	2180	2060	211	767	14.5
235/75R17.5	16	M	6.75	132 129	830	2000	1850	233	803	14
275/70R22.5	18	L	8.25	148 145	900	3150	2900	276	958	21

TRUCK & BUS TIRE

GM216

Excellent traction, Long service life, On the non-paved roads have better resistance to tearing and cutting ability.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
315/80R22.5	20	L	9.00	156 150	850	4000	3350	312	1082	22

TRUCK & BUS TIRE


GM215


Ultra drive and brake ability, tearing resistance, cutting resistance, abrasion resistance, good load capacity, mixed road surface and generally topdress, medium and short vehicles use, suitable for driving wheel, drag wheels.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11R22.5	14	M	8.25	144 142	720	2800	2650	279	1065	22
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1065	22
11R24.5	14	M	8.25	146 143	720	3000	2725	279	1116	22
11R24.5	16	M	8.25	149 146	830	3250	3000	279	1116	22
225/70R19.5	14	M	6.75	128 126	760	1800	1700	226	811	18
245/70R19.5	16	J	7.5	135 133	830	2180	2060	248	839	18
285/75R24.5	14	L	8.25	144 141	760	2800	2575	283	1056	22
295/75R22.5	14	M	9.00	146 143	830	3000	2725	298	1020	22

TRUCK & BUS TIRE

GM217

Ultra drive and brake ability, tearing resistance, cutting resistance, abrasion resistance, good load capacity, mixed road surface and generally topdress, medium and short vehicles use, suitable for driving wheel, drag wheels.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
6.50R16	12	J	5.50F	110 105	670	1060	925	185	750	15
7.00R16LT	14	K	5.50F	118 114	770	1320	1180	200	775	15
7.50R16LT	14	K	6.00G	122 118	770	1500	1320	215	815	15.5
8.25R16LT	16	K	6.50H	128 124	770	1800	1600	235	865	17.5
8.25R20	16	J	6.5	139 137	930	2430	2300	236	974	17.5
9.00R20	16	J	7.0	144 142	900	2800	2650	259	1030	18.5
10.00R20	18	J	7.5	149 146	930	3250	3000	278	1065	19
11R22.5	16	J	8.25	146 143	830	3000	2725	279	1065	21
11.00R20	18	J	8.0	152 149	930	3550	3250	293	1085	19.5
12.00R20	20	J	8.5	156 153	900	4000	3650	315	1125	20.5

TRUCK & BUS TIRE

GM218

Suitable for driving wheel position; Designed for short&middle distance market; Open shoulder design provides excellent traction in wet&dry Conditions; Full-depth siping provides excellent performance throughout the life of the tread; Heavy duty casing for stability and promotion of retreading;

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
12R22.5	18	L	9.00	152 149	930	3550	3250	300	1096	21.5

TRUCK & BUS TIRE

GM302

Generous tread pattern blocks, ultra deep pattern design, provide the strong power. Tire adopts super structure, excellent bearing capacity. Long life, wear-resisting, resistance, Suitable for mining, mountain road.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
10.00R20	16	F	7.5	149 146	930	3250	3000	278	1065	25
11.00R20	18	F	8.0	152 149	930	3550	3250	293	1085	25
12.00R20	20	F	8.5	156 153	900	4000	3650	315	1125	25

TRUCK & BUS TIRE


GM301


High speed, high load, lateral spreads, wet resistance, small rolling resistance, Suitable for the trailer wheels.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
11R22.5	14	M	8.25	144 142	720	2800	2650	279	1054	10.3
11R22.5	16	M	8.25	148 145	830	3150	2900	279	1054	10.3
11R24.5	14	M	8.25	146 143	720	3000	2725	279	1104	10.3
11R24.5	16	M	8.25	149 146	830	3250	3000	279	1104	10.3
285/75R24.5	14	L	8.25	144 141	760	2800	2575	283	1050	10.3
295/75R22.5	14	L	9.00	144 141	760	2800	2575	298	1014	10.3
295/75R22.5	16	M	9.00	146 143	830	3000	2725	298	1014	10.3

TRUCK & BUS TIRE

GM303

Generous tread pattern blocks, ultra deep pattern design, provide the strong power. Tire adopts super structure, excellent bearing capacity. Long life, wear-resisting, resistance, Suitable for mining, mountain road.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
7.50R16LT	14	F	6.00G	122 118	770	1500	1320	215	805	18
8.25R16LT	16	F	6.50H	128 124	770	1800	1600	235	855	18
11.00R20	18	F	8.0	152 149	930	3550	3250	293	1085	25
12.00R20	20	F	8.5	156 153	900	4000	3650	315	1125	25

TRUCK & BUS TIRE ***GM305***



Suitable for off the road with extra deep tread depth; Excellent structure ensures wear resistance and heavy loads; Long mileage with strong traction.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
9.00R20	16	F	7.00	144 142	900	2800	2650	259	1030	25
11.00R20	18	F	8.00	152 149	930	3550	3250	293	1096	25
12.00R20	18	F	8.50	154 151	830	3750	3450	315	1136	25

TRUCK & BUS TIRE ***GM306***



Designed for mining road; Special huge block pattern has excellent traction; Excellent durability and wearing ability with special tread formula.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
10.00R20	18	F	7.50	149 146	930	3250	3000	278	1065	24
11.00R20	18	F	8.00	152 149	930	3550	3250	293	1096	24
12.00R20	20	F	8.50	156 153	900	4000	3650	315	1136	24



TRUCK & BUS TIRE ***GM580***



Excellent durability, Good ground prasing capacity, Low heat generation, Suitable for medium and long mileage vehicles running on the paved road with a standard load.

Size	Ply	Speed Rating	Standard Rim	Load Index	Inflation Pressure (kpa)	Load Capacity (kg)		Section Width (mm)	External Diameter (mm)	Tread Depth (mm)
						Single	Dual			
12.00R24	20	K	8.5	160 157	900	4500	4125	315	1226	14