| System<br>Basic Information | Suitable for daily power consumption : >210 Allowable max loads power : 700VA  | HW00                          |  |
|-----------------------------|--|-------------------------------|--|
| Solar panel  (Mono)         | FS350W mono solar panel Vmp:38.39V Voc:47.13V Imp 9.25A Size: 1956*992*40mm 25 years life time (CE TUV) Coated steel Glass:3.2mm Tem pered Terminal block: IP65 with MC4 connector Efficiency performance:25 years 80 % 20 year 85% 10 years 90% | QTY<br>1pc<br>Price<br>\$108  | SP-500WS Mono panel complete system price USD767             |
| Hybrid solar Inverter       | Solar inverter with controller build it Inverter power:SC500w/24V(sine wave) PV controller:20A/24VLCD display, With AC charger 10A 100% USA brand MOS materials Output:110v,120v,220v,230v,240v(optional) Product size:430*145*224mm             | QTY<br>1pc<br>Price<br>\$170  | Full set: Total volume:0.45CBM Total weight:85KG  Connection |
| Gel Battery                 | Capacity:12V/150AH full sealed Solar power gel battery, Service life:6-8 years , Size:483*170*219mm Connect way:2pcs connect in series connect to solar hybrid inverter  | QTY<br>2pcs<br>Price<br>\$354 | Battery  advantage:  |
| panel rack                  | Slope Rooftop or Flat rooftop including complete fittings wind load:55m/s,snow load:1.5kn/m2 structure:Anodized Aluminum+stainless steel, Angle adjustable (other type of rack can be customized as per client's requirement)                    | QTY<br>1set<br>Price<br>\$55  | Training team and installation service                       |
| Cables                      | 1)1pc 16mm2*35cm battery cable 4pcs 16mm2*2M battery cable 2)4mm2 PV cable 25M * 2pcs 3)terminals and MC4 4)2P 32A Power switch  | QTY<br>1set<br>Price<br>\$110 |  |

| System<br>Basic Information | Suitable for daily power consumption : >4 Allowable max loads power : 1.4KVA  | 4200WH                        |  |
|-----------------------------|---|-------------------------------|--|
| Solar panel                 | FS350W mono solar panel  Vmp:38.39V Voc:47.13V Imp 9.25A  Size : 1956*992*40mm  | QTY<br>2pcs<br>Mono Price     |  |
| (Mono)                      | 25 years life time (CE TUV)  Coated steel Glass:3.2mm Tem pered Terminal block: IP65 with MC4 connector Efficiency performance :25 years 80 % 20 year 85% 10 years 90%  | \$216                         | SP-1KWS  |
| Hybrid solar Inverter       | inverter with controller built it   | QTY                           | Mono panel complete system price USD954  |
|                             | Wall type Inverter power:1kw/24v  PV controller:30A/24V,AC charge:10-15A  100% USA brand MOS materials  Double protection, easy after sales service  O/P:110V,220VAC and 5V/12VDC  Product size:480*270*185mm                 | 1pc<br>Price<br>\$219         | Remote monitoring: 110USD( optional )  Full set: Total volume:0,55CBM  |
| Gel Battery                 | Capacity:12V/150AH full sealed Solar power gel battery, Service life:6-8 years , Size:483*170*219mm Connect way:2pcs connect in series connect to solar hybrid inverter   | QTY<br>2pcs<br>Price<br>\$344 | Total weight:180KG  Connection   |
| panel rack                  | Slope Rooftop or Flat rooftop including complete fittings wind load:55m/s,snow load:1.5kn/m2 structure:Anodized Aluminum+stainless steel, Angle adjustable (other type of rack can be customized as per client's requirement) | QTY<br>1set<br>Price<br>\$110 | State Posset  Name Insurance worth Scientific Science (see Agreement Agreeme |
| Cables                      | 1)1pc 16mm2*35cm battery cable,<br>4pcs 16mm2*2M battery cable.<br>2)4mm2 PV cable 50M,25M black 25M red.<br>3)1set PV terminals and MC4<br>4)1P 63A Battery switch and box   | QTY 1set Price \$165          | team and installation service  |

| Ot  | ff Grid Solar Home System S  |              |   |
|---|--|--------------|---|
| System  | Suitable for daily power consumption : >8.4KWH                                 |              | HEHE TO BE AND CO                       |
| Basic Information   | Allowable max loads power : 2KW(=2.8K  | VA)          |   |
| Solar panel   | FS350W mono solar panel  | QTY          | i gu                                    |
|   | Vmp:38.39V Voc:47.13V Imp 9.25A  | 4pcs         | 51 M                                    |
| 200000  | Size : 1956*992*40mm   |              |   |
|   | 25 years life time (CE TUV)  | Mono Price   |   |
| 1 2222222222 1240<br>1 2222222222 1240<br>1 2222222222 1240 | Coated steel Glass: 3.2mm Tem pered  | \$412        | ) . <u></u>                             |
| " 12222222222 1236  | Terminal block: IP65 with MC4 connector  Efficiency performance :25 years 80 % | 10           |   |
| (8.5  | 20 year 85% 10 years 90%   |              |   |
| (Mono)  | Connect way:each 2 pcs in series   |              | 2kw solar system in Mozambique          |
| United a plan because                                       |  | OTV          | SP-2KWS                                 |
| Hybrid solar Inverter                                       | Wall type Inverter power:2kw/48v   | QTY          | Mono panel complete system              |
|   | PV Controller model:48v/40A  | 1pc<br>Price | price USD1857                           |
|   | AC charger :10-15A 100% USA brand MOS materials                                | \$392        |   |
|   | Double protection, easy after sales service                                    | φ332         | Remote monitoring:                      |
|   | O/P:110V,220VAC and 5V/12VDC   |              | 110USD( optional )                      |
|   | Product size: 480*270*185mm  |              | man and                                 |
| Gel Battery   | Capacity:12V/150AH   | QTY          | Full set: Total volume:1.03CBM          |
|   | full sealed Solar power gel battery,   | 4pcs         | Total weight:389KG                      |
|   | Service life:6-8 years ,   | Price        | Total Weight. 303KG                     |
| mercan is a   | Size:483*170*219mm   | \$698        |   |
|   | Connect way:4pcs connect in series connect                                     |              |   |
|   | to solar hybrid inverter   |              |   |
| panel rack  | Slope Rooftop or Flat rooftop  | QTY          | Connection                              |
|   | wind load:55m/s,snow load:1.5kn/m2   | 1set         | -                                       |
|   | structure: Anodized Aluminum+stainless steel,                                  | Price        |   |
|   | Angle adjustable   | \$200        | Solar Panel                             |
|   | (other type of rack can be customized as per                                   |              | Solar loverier with Built-in Controller |
|   | client's requirement )   |              |   |
| Cables  | 1) 3pcs 16mm2*35CM battery cable   | QTY          | Home Appliances                         |
|   | 4pcs 16mm2*2M battery cable  | 1set         |   |
|   | 2)4mm2 PV cable <b>50M*2pcs</b>  | Price        | Generator                               |
|   | 3)terminals and MC4+1 <b>P63A Power switch</b>                                 | \$185        | Battery                                 |
|   |  |              | advantage:                              |
|   |  |              | Training team and installation          |
|   |  |              | service                                 |

| System<br>Basic Information | Suitable for daily power consumption : >12.6K<br>Allowable max loads power : 3KW(=4.2KVA)   |                               |  |
|-----------------------------|---|-------------------------------|--|
| Solar panel                 | FS350W mono solar panel Vmp:38.39V Voc:47.13V Imp 9.25A Size: 1956*992*40mm 25 years life time (CE TUV) Coated steel Glass:3.2mm Tem pered Terminal block: IP65 with MC4 connector Efficiency performance:25 years 80 % 20 year 85% 10 years 90% Connect way:each 2 pcs in series | Mono<br>Price<br>\$618        | SP-3KWS  Mono panel complete system  |
| PV combiner PV COMMINER PDX | Model:H4T-48V Simplify wiring between PV array and controller.  Prevent hot spot effect thunderstorm& surge protection Product Size:360*345*145mm   | QTY<br>1pc<br>Price<br>\$197  | price USD2927  Remote monitoring: 110USD( optional )   |
| Hybrid solar Inverter       | Wall type Inverter power:3kw/48V PV Controller model:48v/60A AC charger :10-15A 100% USA brand MOS materials Double protection, easy after sales service O/P:110V,220VAC and 5V/12VDC Product size:480*270*185mm  | QTY<br>1pc<br>Price<br>\$487  | Full set: Total volume:1.56CBM Total weight:453KG  |
| Gel Battery                 | Capacity:12V/200AH full sealed Solar power gel battery, Service life:6-8 years Size:522*240*219mm Connect way: 4pcs battery in series is each string.   | QTY<br>4pcs<br>Price<br>\$790 | Connection   |
| panel rack                  | Slope Rooftop or Flat rooftop wind load:55m/s,snow load:1.5kn/m2 structure:Anodized Aluminum+stainless steel, Angle adjustable (other type of rack can be customized as per client's requirement)   | QTY<br>1set<br>Price<br>\$200 | Notes Faces  Notes |
| Cables                      | 1) 3pcs 16mm2*35CM battery cable 2pcs 16mm 2M battery cable 16mm 10M power cable 2)4mm2 PV cable 50M*2pcs   | QTY<br>1set<br>Price<br>\$195 | advantage: Training team and installationservice   |

|                           | Off Grid Solar Home System SP-5K  | WS Suitable                    |  |
|---------------------------|---|--------------------------------|--|
| System  Basic Information | for daily power consumption : >25.2KWH Al loads power : 5KW(=7KVA)  | lowable max                    |  |
| Solar panel               | FS350W mono solar panel Vmp:38.39V Voc:47.13V Imp 9.25A   | QTY<br>12pcs                   |  |
|                           | Size: 1956*992*40mm 25 years life time (CE TUV)  Coated steel Glass:3.2mm Tem pered Terminal block: IP65 with MC4 connector  Efficiency performance: 25 years 80 % 20                             | Mono Price<br>\$1100           | The lower had been been been been been been been bee   |
| (Mono)                    | year 85% 10 years 90%  Connect way:each 4 pcs in series   |                                | Mono panel complete system price USD4961   |
| PV Array Combiner         | Model:H4T-96v Multiple PV strings inputs. Simplify wiring between PV array and controller. Prevent hot spot effect Reliable thunderstorm& surge protection Product Size:360*345*145mm             | QTY<br>1pc<br>Price<br>\$200   | Remote monitoring:<br>110USD( optional )   |
| Solar Controller          | PV controller model:96V/60A Charging efficiency; 90%-95%, charging mode, intelligent control., various protection functions;  | QTY<br>1pc<br>Price<br>\$145   | Full set: Total volume:2.8CBM Total weight:663KG   |
| IGBT sine wave Inverter   | IGBT Inverter:5KW96VDC  110V/120V/220V/230V/240VAC output,  City power and generator charger build in Overload, overcharge, over-discharge protection Fuji brand IGBT material                    | QTY<br>1pc<br>Price<br>\$855   |  |
| Gel Battery               | Capacity:12V/200AH full sealed Solar power gel battery, Service life:6-8 years Size:522*240*219mm Connect way: 8pcs battery in series   | QTY<br>8pcs<br>Price<br>\$1620 | Marendomorphisms Tymmin Same and Same a |
| panel rack                | Slope Rooftop or Flat rooftop wind load:55m/s,snow load:1.5kn/m2 structure:Anodized Aluminum+stainless steel, Angle adjustable (other type of rack can be customized as per client's requirement) | QTY<br>1set<br>Price<br>\$380  | advantage: Training team and installation service  |
| Cables                    | 1)7pcs 16mm2*35CM,2pcs 16mm2*2M battery cable, 16mm *20M cable. 2)4mm2 PV cable 100M, (black+ red) 3)1set PV terminals and MC4 4)2P 63A Battery switch and box                                    | QTY<br>1set<br>Price<br>\$231  |  |

| System<br>Basic Information | Suitable for daily power consumption : >33<br>Allowable max loads power : 8KW(=11.4K  |                                      |  |
|-----------------------------|---|--------------------------------------|--|
| Solar panel  (Mono)         | FS350W mono solar panel(poly optional)  Vmp:38.39V Voc:47.13V Imp 9.37A  Size: 1956*992*40mm  25 years life time (CE TUV)  Coated steel Glass:3.2mm Tem pered  Efficiency performance:25 years 80 %  20 year 85% 10 years 90%  Connect way:each 4 pcs in series | QTY<br>16pcs<br>Mono Price<br>\$1500 | Training Till and grant and all year proteins the land of the the l |
| PV Array Combiner           | Model:H4T-96v Multiple PV strings inputs<br>and controller, Prevent hot spot effect<br>Reliable thunderstorm& surge protection<br>Product Size:400*425*145mm  | QTY 1pc Price \$200                  | SP-8KWS<br>Mono panel complete system<br>price USD6995   |
| Solar Controller            | PV controller model:96V/60A Charging efficiency; 90%-95%, charging mode, intelligent control., various protection functions;  | QTY<br>1pc<br>Price<br>\$145         | Remote monitoring: 110USD( optional )  Full set: Total volume:3.2CBM   |
| Pure sine wave Inverter     | Inverter:8KW96VDC  110V/120V/220V/230V/240VAC output, City power and generator charger build in Overload, overcharge, overdischarge protection Fuji brand IGBT material   | QTY<br>1pc<br>Price<br>\$1,000       | Total weight: 1140KG   |
| Gel Battery                 | Capacity:12V/150AH full sealed Solar power gel battery, Service life:6-8 years Size:483*170*219mm Connect way: 8pcs battery in series is each string. 2 strings connect to solar hybrid inverter  | QTY<br>16pcs<br>Price<br>\$2792      |  |
| panel rack                  | Slope Rooftop or Flat rooftop<br>wind load:55m/s,snow load:1.5kn/m2<br>structure:Anodized Aluminum+stainless steel,<br>Angle adjustable   | QTY<br>1set<br>Price<br>\$500        | advantage: Training team and installation service  |
| Cables                      | 1) 14pcs 16mm2*35CM battery cable 4pcs 16mm2*2M battery cable 16mm *20M 2)4mm2 PV cable 100M 3)terminals and MC4 4)2P100A switch Box 2pcs   | QTY<br>1set<br>Price<br>\$268        |  |

| System                  | Suitable for daily power consumption : >42  | 2KWH                                 |  |
|-------------------------|---|--------------------------------------|--|
| Basic Information       | Allowable max loads power :10KW(= 14.3  | KVA)                                 |  |
| Solar panel  (Mono)     | FS350W mono solar panel Vmp:38.39V Voc:47.13V Imp 9.37A Size: 1956*992*40mm 25 years life time (CE TUV) Coated steel Glass:3.2mm Tem pered Efficiency performance:25 years 80 % 20 year 85% 10 years 90% Connect way:each 4 pcs in series | QTY<br>20pcs<br>Mono Price<br>\$1950 | Patent Mar principal data from the control of the c |
| PV Array Combiner       | Model:H6T-96v Multiple PV strings inputs and controller, Prevent hot spot effect Reliable thunderstorm& surge protection Product Size:400*425*145mm   | 1pc<br>Price<br>\$427                | SP-10KWS<br>Mono panel complete syst<br>price USD8342  |
| Solar Controller        | PV controller model:96V/100A Charging efficiency; 90%-95%, charging mode, intelligent control., various protection functions;   | QTY<br>1pc<br>Price<br>\$260         | Remote monitoring:<br>110USD( optional )   |
| Pure sine wave Inverter | Inverter:10KW96VDC 110V/120V/220V/230V/240VAC output, City power and generator charger build in Overload,overcharge, over-discharge protection Fuji brand IGBT material   | QTY<br>1pc<br>Price<br>\$1130        | Full set:<br>Total volume:4.72CBM<br>Total weight:1520KG   |
| Gel Battery             | Capacity:12V/200AH  full sealed Solar power gel battery,  Service life:6-8 years Size:522*240*219mm  Connect way: 8pcs battery in series is each string. 2 strings connect to solar hybrid inverter                                       | QTY<br>16pcs<br>Price<br>\$3940      |  |
| panel rack              | Slope Rooftop or Flat rooftop wind load:55m/s,snow load:1.5kn/m2 structure:Anodized Aluminum+stainless steel, Angle adjustable  | QTY<br>1set<br>Price<br>\$620        |  |
| Cables                  | 1) 14pcs 16mm2*35CM battery cable 4pcs 16mm2*2M battery cable 16mm *20M 2)4mm2 PV cable 150M 3)terminals and MC4 4)2P100A switch Box 2pcs   | QTY<br>1set<br>Price<br>\$315        | advantage: Training team and installation service  |

|                           | Off Grid Solar Home System SP15  | The second second second             |  |
|---------------------------|--|--------------------------------------|--|
| System  Basic Information | for daily power consumption : >67.2KWH loads power : 15KW(=21.4KVA)  | Allowable max                        |  |
| Solar panel  (Mono)       | FS380W mono solar panel Vmp:38.39V Voc:47.13V Imp 9.25A Size: 1956*992*40mm 25 years life time (CE TUV) Coated steel Glass:3.2mm Tem pered Terminal block: IP65 with MC4 connector Efficiency performance:25 years 80 % 20 year 85% 10 years 90% Connect way:each 8pcs in series | QTY<br>28pcs<br>Mono Price<br>\$3260 | SP-15KWS  Mono panel complete system                   |
| PV DC cabinet             | Model: H4T-192v Multiple PV strings inputs and controller Prevent hot spot effect Reliable thunderstorm& surge protection Product Size: 400*425*145mm  | QTY 1pc Price \$570                  | price USD11,341  Remote monitoring: 110USD( optional ) |
| Controller                | PV controller model:192V/80A Charging efficiency; 90%-95%, charging mode, intelligent control., various protection functions;  | QTY<br>1pc<br>Price<br>\$518         | Full set: Total volume: 6.6CBM Total weight: 2180KG    |
| IGBT Inverter             | Pure sine wave inverter;15kw, DC input:192v AC charger 15-20A 100% Germany brand IGBT materials Double protection, easy after sales service O/P:110V,220VAC Product Size:590*470*730mm   | QTY<br>1pc<br>Price<br>\$1998        |  |
| Gel Battery               | Capacity:12V/250AH full sealed Solar power gel battery, Service life:6-8 years ,Size:483*170*219mm Connect: 16pcs battery in series is each string.  | QTY<br>16pcs<br>Price<br>\$3980      | 100 100 100 100 100 100 100 100 100 100                |
| Panel rack                | Slope Rooftop or Flat rooftop wind load:55m/s,snow load:1.5kn/m2 structure:Anodized Aluminum+stainless steel, Angle adjustable   | QTY<br>1set<br>Price<br>\$890        | advantage: Training team and installation service      |
| Cables                    | 1) 14pcs 16mm2*35CM battery cable 2pcs 16mm2*2M battery cable 16mm 20M power cable 2)4mm2 PV cable 200M 3)terminals MC4+2P 100A Power switch box   | QTY<br>1set<br>Price<br>\$395        |  |

| System                              | Off Grid Solar Home System SP Suitable for daily power consumption : >80   |                            |  |
|-------------------------------------|--|----------------------------|--|
| Basic Information                   | Allowable max loads power: 20KW(=28K\  |                            | TSP20KW solar fectory project in Thailand  |
| Solar panel                         | FS380W mono solar panel Vmp:38.39V Voc:47.13V Imp 9.75A Size: 1956*992*40mm 25 years life time (CE TUV)  | QTY<br>35pcs<br>Mono Price |  |
| Mono)                               | Coated steel Glass:3.2mm Tem pered Terminal block: IP65 with MC4 connector Efficiency performance :25 years 80 % 20 year 85% 10 years 90% Connect:each 7pcs in series, 5 strings in series | \$3925                     | 20kw solar system installed in Tha   |
| V DC cabinet                        | Model:H6T-192v Multiple PV strings inputs  | QTY                        | Mono panel complete syste  |
|                                     | and controller, Prevent hot spot effect  | 1pcs                       | price USD15,257  |
|                                     | Reliable thunderstorm& surge protection  | Price                      |  |
| CANCEL STENSON                      | Product Size:400*425*145mm   | \$657                      | Remote monitoring:   |
| ontroller                           | PV controller model:192V/100A  | QTY                        | 110USD( optional )   |
|                                     | Charging efficiency; 90%-95%,  | 1pc                        |  |
|                                     | charging mode, intelligent control.,   | Price                      |  |
|                                     | various protection functions;  | \$510                      | Full set:  |
| ure sine wave Inverter              | Pure sine wave inverter;20kw DC input:192v   | QTY                        | Total volume:7.4CBM  |
| -                                   | AC charger 15-20A  | 1pc                        | Total weight: 3327KG   |
|                                     | 100% Germany brand IGBT materials  | Price                      | ,  |
|                                     | Double protection, easy after sales service O/P:110V,220VAC 50HZ or 60HZ Product Size:590*470*730mm  | \$2810                     | - 60   |
| el Battery                          | Capacity:12V/200AH   | QTY                        | # 4  |
|                                     | full sealed Solar power gel battery  | 32pcs                      | 93 + 109   |
|                                     | Service life:6-8 years   | Price                      |  |
| •                                   | Size:522*240*219mm  Connect way: 16pcs battery in series is each string. 2 string connect to inverter and controller   | \$6980                     |  |
| anel ground rack                    | Slope Rooftop or Flat rooftop  | QTY                        |  |
| A PRODUCTION OF THE PERSON NAMED IN | wind load:55m/s,snow load:1.5kn/m2   | 1set                       | A STATE OF THE STA |
|                                     | structure:Anodized Aluminum+stainless steel,   | Price                      | advantage:   |
|                                     | Angle adjustable(other type of rack can be customized as per client's requirement)   | \$1400                     | Training team and installation   |
| ables                               | 1) 30pcs 16mm2*35CM battery cable  | QTY                        | service  |
|                                     | 4pcs 16mm2*2M battery cable  | 1set                       |  |
|                                     | 25mm 20M power cable   | Price                      |  |
|                                     | 2)4mm2 PV cable 100M*2pcs 3)terminals MC4+2P 100A Power switch box   | \$415                      |  |

|                            | Off Grid Solar Home System SP30   | KWS                                     |   |
|----------------------------|---|---|---|
| System Basic Information   | Suitable for daily power consumption : >118k  | WH                                      |   |
| Solar panel  (Mono)        | FS380W mono solar panel Vmp:38.39V Voc:47.13V Imp 9.75A Size: 1950*992*40mm 25 years life time (CE TUV) Coated steel Glass:3.2mm Tem pered Terminal block: IP65 with MC4 connector Efficiency performance:25 years 80 % 20 year 85% 10 years 90% Connect:each 13pcs in series | QTY<br>52pcs<br>Mono<br>Price<br>\$5440 | SP-30KWS Mono panel complete system price USD24,854 |
| PV Array Combiner          | Model:H4T-360v Multiple PV strings inputs and controller,Prevent hot spot effect Reliable thunderstorm& surge protection Product Size:360*345*145mm   | QTY<br>1pc<br>\$657                     | Remote monitoring:<br>110USD( optional )            |
| Controller                 | PV controller model: 360V/100A Charging efficiency; 90%-95%, charging mode, intelligent control., various protection functions; Can read daily,monthly and total power generation   | QTY<br>1pc<br>\$672                     | Full set: Total volume:13CBM Total weight:5850KG    |
| IGBT sine wave Inverter    | Pure sine wave inverter 30KW/360VDC input  AC charger 15-20A  100% Germany brand IGBT materials  Product size:785*580*1197mm Weight:350KG  Output: 220V 380V 415V 50/60HZ   | QTY<br>1pc<br>\$3900                    |   |
| Gel Battery                | Capacity:12V/200AH full sealed Solar power gel battery, Service life:6-8 years, Size:522*240*219mm Connect way: each 30pcs in series, 2 strings in parallel   | QTY<br>60Pcs<br>\$12400                 | ## 12   |
| panel rack  (Slope) (Flat) | Slope Roof or Flat roof or Ground (option) including complete fittings wind load:55m/s,snow load:1.5kn/m2 structure: Anodized Aluminum +stainless steel, Angle adjustable(other type of rack can be customized as per client's requirement)                                   | QTY<br>1set<br>\$1960                   | advantage: Training team and installation service   |
| Cables                     | 1)58pcs 16mm2*35CM battery cable 4pcs 16mm2*2M battery cable 25mm 20M power cable 2)4mm2 PV cable 100M*2pcs 3)terminals and MC4+2P 100A Power switch box  | QTY<br>1set<br>Price<br>\$475           |   |



Install support:



package and shipment:



## project:

