



Mortuary Freezer

Model No.: 6 Rooms.

Product Overview

RD-6 Mortuary Freezer

The mortuary refrigerator is the major product for mortuary line.



Mainly Characteristics:

- Drop in self-contained refrigeration system. It with digital thermometer and easy to adjust(-15°C to 5°C) temperature controller.
- The unit ships fully assembled. Plug unit into an outlet and the unit is workable.
- Heavy-quality stainless steel material for long lasting use.
- Single door is with single control. Each room has an independent refrigeration and temperature control system.
- It has independent detachable tray.
- Safety lock and alarm function.

Feature

- **Insulation Technology**

8 cm foamed in place urethane
It is a green/ environmental foam material.
Disposable foam machine overall.



- **Cooling quality**

High quality compressor (Germany Compressor is optional) to be sure the necessary temperature.



- **Safety door**

Safe door locked system, with lock keys. Unique door seal design for the minimum loss of cold temperature during a door opening. Door seal belt can be replaced. Door frame with a unique one-piece design



- **Removable Tray**

Separate body tray with the strong sliding system to make sure easy to pull out and pull back. Note: All the body trays (mortuary refrigerator, lifting cart, walk-in rack) size is the same. Our products are a series of products, the tray is the universal size (same size).



- **Alarm function**

The alarm function is applicable to the following: .
Unique door seal design for the minimum loss of cold temperature during a door opening. Door seal belt can be replaced.
Door frame with a unique one-piece design



- **Installation**

Unit ships fully assembled; simply plug unit into an outlet and the unit is operational.



Product Specification	
Model	RD-6
Capacity	6 rooms
Product size	2060(L)*1580(W)*1975(H)mm,
Packing size	2140*1620*2075 (mm);
Container loading	3 sets/20GP, 7sets/40GP
Inner size	1950(L)*630(W)*440(H)mm
Body tray	1940(L)*580(W), 0.8mm thickness, loading: 200kg
Refrigeration system	Single door single control, independent refrigeration system.
Compressor	German SECOP origin compressor, Model: NL7CLX
Temperature control	Computer micro-control system, -15 to 5°C, accuracy 0.1°C
Material	S.S201 (S.S.304 for choose)
Steel parameters	Outer thickness 1.0mm, inner thickness 0.8mm, for better cooling performance.
Insulating layer	Polyurethane foam integrated by machine, arc door design. Polyurethane thickness 80mm
Alarm system	7 scenarios,3 modes alarm
Lighting system	Auto-open with door open, 35W
Voltage range	Range: 187-240V, AC, Standard 220V, 50Hz.(110V/60Hz)
Power	1440W
Working temperature	10-38°C;
Anti-shock level	Class 1



10 YEARS FOCUS ON Funeral Pathology Industry .

90 COUNTRIES EXPORTED

1 YEARS AFTER-SALES SERVICE + Lifelong technical support.

10 + CE certification

