

Explosion - proof wireless audio and video life detector



Technical data:1, the whole machine:

- ★ audio and video combined, highly integrated: the data presented on the same display;
- ★ explosion-proof,suitable for hazard explosive environments after the earthquake and other accidents, explosion-proof grade Exib IIB T4GB;
- ★ wireless transmission, , disaster relief scene can be wirelessly transmitted to the disaster relief headquarters, configure the wireless video receiver, storage 8GB, can store search video;
- ★ six audio probe, a larger search range: the audio probe can be distributed in the disaster area layout, increasing the search area, improve search efficiency, save more in distress!

Multi-angle video probe: the original camera can be seamless 360 ° horizontal rotation, 360 ° viewing angle, vertical 270 ° , effectively increasing the search range and accuracy.

2, the control host:

Peak tracking: The yellow peak tracking procedure determines the maximum

Battery Display: The battery level is always displayed

A key switch: audio, video, a key switch

Push to talk (push to talk) function: to communicate with the buried

Large screen: 7 "TFT highlight screen

Resolution: 768 × 512

Working time: more than 3 hours of continuous use (depending on the environment).

Charging time: 4hr (depending on temperature, current intensity and other factors may be)

AC voltage charger: 220V

Operating temperature: -30 °C - +60 °C, low temperature quick start.

3, wireless audio probe:

- ★ transmission: wireless
- ★ transmission distance: $\geq 100\text{m}$

Search area: 600 m²

★ number of probes: 6pcs

Audio range: 1Hz-3000Hz

Protection class: IP67

Working time: ≥8H

weight:

size:

4, color rotating camera:

Angle of view: 360 ° horizontal, 360 ° viewing angle, vertical 270 ° field of view

1/4 "CCD, 0.5 lux, 380 lines, objective: f-2.0 mm, F-2.0;

Lens diameter: 51mm Type: color CCD

Light source: 8 imported infrared light.

Size: 51mm × 99mm, weight: 240g

Waterproof: I64 waterproof standard

With quick-swap interface, you can quickly replace.

5 waterproof infrared camera:

In the dark,the visual distance of up to 6m.

Waterproof level: IP67

With quick-swap interface, you can quickly replace.

6, the probe rod:

Probe length: 4 sections can be extended 1-2.38m

With 5m cable, anti-off plug; (optional 20 meters, 30 meters cable)

The head is free to bend;