

stck	material	thickn.	width	length	weight	quality	defect
1	cold rolled coil fullhard	1,71	1386	coil	18,283	fullhard	rusty + thickness variation 1,60mm to 4,17mm
1	cold rolled coil fullhard	1,75	1062	coil	11,840	fullhard	rusty + thickness variation 1,24mm to 2,77mm
1	cold rolled coil fullhard	2,12	931	coil	18,600	fullhard	rusty
1	cold rolled coil fullhard	2,14	1276	coil	12,615	fullhard	rusty + thickness variation 1,16mm to 4,20mm
1	cold rolled coil fullhard	2,25	1098	coil	12,192	fullhard	rusty
1	cold rolled coil fullhard	2,76	1500	coil	15,930	fullhard	rusty + thickness variation
1	cold rolled coil, soft	0,65	878	coil	11,638	DC 04	
1	cold rolled coil, soft	0,98	1641	coil	13,370	HC420LA	surface defect
1	cold rolled coil, soft	0,99	750	coil	11,260	DC 01	
1	hot dipped galvanized coil	0,40	1250	coil	20,050	DX51D+Z100MAC	
1	hot dipped galvanized coil	0,70	680	coil	9,825	DX56D+Z100MBO	
1	hot dipped galvanized coil	0,70	1190	coil	10,310	HX380LAD+Z	slightly rusty
1	hot dipped galvanized coil	0,92	1580	coil	8,724	GXES+Z140MBO	
1	hot dipped galvanized coil	2,50	1500	coil	16,470	DX51D+Z275MAC	whiterust
1	prepainted coil	1,00	1504	coil	8,667	Color: black-grey	
1	prepainted coil	1,17	1283	coil	8,362	Color: brown-brown	partly uncolored

208,136

PICTURES ARE ATTACHED IN PDF FILE