

Customers



Main distribution countries:

-  **France**
-  **Germany**
-  **Italy**
-  **Belgium, Netherland**





Reliable Test Facility



Rain test



Hill climbing test



Shock Absorption Test



Device testing

Our Model



Key Advantages



SQ4

Size:2310*1100*1540MM
2300*1000*1495MM
Motor:1500W2000W3000W
Speed:25/45km
Range:60-120KM



Q7

Size:2400*1125*1610MM
Motor:2500W
Speed:25/45km
Range:60-120KM



Q3

Size:2250*1205*1650MM
Motor:2500W
Speed:25/45km
Range:60-120KM



SQ3

Size:2260*1000*1510MM
2310*1100*1545MM
Motor:1500W2000W3000W
Speed:25/45km
Range:60-120KM

Our Model



Key Advantages

THE
Candy
CAR **CC**

Size:1595*670*1700MM
Motor:1000W
Speed:35km
Range:60KM

THE
Candy
CAR **SM**

Size:2820*900*1600MM
Motor:2000W3000W
Speed:45/60km
Range:60-120KM

THE
Candy
CAR **AFW001**

Size:1520*680*1050MM
Motor:1000W
Speed:25km
Range:55KM

THE
Candy
CAR **J2C**

Size:2879*1200*1760MM
Motor:3000W
Speed:50km
Range:140KM

Recently updated

Vehicle Size	3400*1580*2050mm
Curb weight	770kg
Carrying capacity	620kg
Number of passengers	2
Driving form	Rear-guard
Battery type	Lithium iron phosphate
Battery supplier	Tianneng/Binai
Battery capacity	9.6kwh
NEDC range	80km
Maximum speed	80km/h

THE
Candy
CAR



Product advantages

- Small and flexible body, suitable for the last mile of street distribution.
- Fully meet the standards of new energy motor vehicles, and the right of way is legal and prioritized.
- Car gauge-gate car body manufacturing standard. Safety devices such as ABS are standard.
- Major brands manufactures of parts with Gelly quality, and 200,00 extra-long warranty for 5 years
- Provide Class II chassis to meet the customization needs of various end users in logistic industries.

THE
Candy
CAR





New species of terminal logistics



Showcase

“

THE
Candy
CAR

not only affordable, but also superior in performance, and have won praise and recognition from customers all over the world.

”



Warranty



Professional manufacturing for 18 years



All products are guaranteed for two years.

