



# G200RS | Rental Set



DIESEL GENERATOR

STAGE IIIA

ELECTRICAL								
Frequency (Hz)	Phases	Voltage (V)	kVA	Prime		Standby		Rated Speed (RPM)
				kW		kVA	kW	
50	3	400/230V	200	160		220	176	1500
60	3	480/277V	200	160		219	175	1800

POWER FACTOR	
3 Phase	0.8
1 Phase	1

**ALL RATINGS ARE TO STANDARD REFERENCE CONDITIONS ISO 8528**

**Prime:** This rating is for the supply of continuous electrical power, at variable load, in lieu of commercially purchase power. There is no limitation on the annual hours of operation and 10% over load power can be supplied for 1 hour in 12.

**Standby:** Standby Power (ESP) is the maximum output available, for up to 500 hours per year, where the average load (variable) does not exceed 70% of the standby power rating. No overload is available.

**Stage IIIA** models are only emissions compliant at 50Hz Prime Power in accordance with 97-68EC.

**JCB GENERATOR TECHNICAL SPECIFICATIONS.** Tel: +44 (0)1889 272200. [www.jcbgenerators.com](http://www.jcbgenerators.com). JCB reserves the right to change specifications without notice. Illustrations shown may include optional equipment and accessories.

CANOPY		
Lockable Maintenance Access Doors		●
Control Panel Viewing Window		●
Oversized Fork Pockets		●
Single Lift Point		●
Bunding		●
4 Point Tie Down		●
High Density Fire Retardant Foam		●
Yellow Paint		Δ
White Paint		●
Heavy Duty Rental Base		●
Drag Bar		Δ
Galvanised Steel Canopy		●
Standard: ● Not Available: x Optional: Δ		

ALTERNATOR UCI 274H		
Poles	4	
Winding Connections	Star	
Insulation	Class H	
Enclosure	IP23	
Exciter System	Self-regulating brushless	
Voltage Regulator	AVR	
Steady State Voltage Regulation	+/- 1%	
Bearing	Single bearing sealed	
Coupling	Flexible disc	
Cooling	Direct drive centrifugal blower fan	
Coating	Total Protection +	

STARTING SYSTEM		
Battery Capacity	Ah	850
Number of Batteries		1
Auxiliary Voltage	V	12

ENGINE		
1500 RPM		
Net Output Rating (PRP)	kW	169
Net Output Rating (Standby)	kW	187
1800 RPM		
Net Output Rating (PRP)	kW	194
Net Output Rating (Standby)	kW	212
Manufacturer and Model		John Deere 6068HFU82
Fuel		Diesel
Injection		Direct
Aspiration		Turbo Charged
Cylinders		6
Bore and Stroke	mm	106 x 127
Displacement	L	6.80
Cooling		Water
Engine Oil Specification		JCB EP 15W40
Compression Ratio		17.2 : 2
Engine Oil Capacity	L	24.60
Coolant Capacity	L	11.30
Governor		Electronic
Air Filter		Paper Element
Engine Oil Consumption	100% Load	0.1% of fuel consumed

FUEL SYSTEM		
Diesel Specification		EN590
Standard Capacity Fuel Tank	L	515

## FUEL CONSUMPTION

100% Load Prime	L/h	50Hz	46.20
75% Load Prime	L/h		37.30
50% Load Prime	L/h		25.40
100% Load Standby	L/h		48.50
100% Load Prime	L/h	60Hz	47.80
75% Load Prime	L/h		38.00
50% Load Prime	L/h		26.40
100% Load Standby	L/h		51.10

## EXHAUST SYSTEM

Maximum Temperature 100% Standby	°C	50Hz	600.00
Exhaust Gas Flow 100% Standby	m <sup>3</sup> /min		30.12
Maximum Allowed Back Pressure	kPa		7.50
Exhaust Discharge Size	mm	100	

## AIR SYSTEM

Intake Air Flow 100% Standby	m <sup>3</sup> /h	50Hz	597
Total Cooling Air Flow 100% Standby	m <sup>3</sup> /s		5.60

## SOUND PRESSURE

LpA (7m)	50Hz	dB(A)	68
----------	------	-------	----

## MECHANICAL FEATURES

Cooling Pack	●
Air Filter	●
Mechanical Governor	x
Low Oil Pressure Switch	●
Coolant Temperature Sender	●
Oil Temperature Sender	●
Radiator Guards	●
Hot Component Guards	●
Manual Oil Drain Pump (Canopy)	Δ
Water Jacket Heater	Δ
Pre-Filter with Separator	●
Fuel Level Sender	●
Internal Fuel Fill	●
3 Way Fuel Valve	●
Residential Silencer	●
Air Shut-Off Valve	Δ
Electronic Governor	●
Spark Arrestor	Δ
Standard: ●      Not Available: x      Optional: Δ	

# G200RS | Rental Set



## ELECTRICAL FEATURES

AVR DSR	●
AVR DER	x
Winding Protection Standard	x
Winding Protection Standard +	x
Winding Protection Grey	x
Winding Protection Total	x
Winding Protection Total +	●
MAUX	x
PMG	Δ
Anti-Condensation Heater	Δ
3 Pole Moulded Case Circuit Breaker	x
4 Pole Moulded Case Circuit Breaker	●
Earth Leakage Protection (Switchable)	Δ
Preparation for Earth Spike	●
Optional Voltages	Δ
Emergency Stop Button (Control Panel)	●
External Emergency Stop Button	●
AGM Battery	Δ
Socket Panel (1 x 32A – 3ph, 1 x 32A – 1ph, 1 x 16A – 1ph) IP44	x
Socket Panel (1 x 63A – 3ph, 3 x 32A – 1ph) IP44	x
Socket Panel (1 x 63A – 3ph, 1 x 32A – 3ph, 3 x 32A – 1ph) IP44 (1 x 125A – 3ph) IP67	Δ
Bund Alarm / Shut down	Δ
50Hz / 60Hz Switch	Δ
Standard: ● Not Available: x Optional: Δ	

## BATTERY FEATURES

Battery Isolator	●
Battery Type	Sealed Lead Acid
Battery Charger	Δ

## JCB COMMUNICATION AND CONTROL

DSE 7320	●
DSE 8610 synchronising controller	Δ
LiveLink for Power	●
Standard: ● Not Available: x Optional: Δ	

## WEIGHT AND DIMENSIONS

Length	mm	3800
Width	mm	1270
Height	mm	2033
Shipping Volume (sea ready)	m <sup>3</sup>	9.80
Weight*	Kg	3500

\*Standard build with all fluids except fuel

## CE PACK

EMC Certification	●
Hot Guards	●
Belt Guards	●
Sound Power Decal	●
EU Declaration for Engine Emissions	●
Complete Machine Declaration of Conformity	●
Standard: ● Not Available: x Optional: Δ	

## REFERENCE STANDARDS

JCB Generators are CE certified and conform to the following Directives (subject to a country requiring such standard):

- EN 12100, EN 13857, EN 60204
  - 2006/42/CE Machinery safety
  - 2006/95/EC Low voltage
  - 2004/108/CE Electromagnetic compatibility
  - 2000/14/EC Sound Power Level (amended by 2005/88/EC)
  - 97/68/EC Emissions (amended by 2002/88/EC & 2004/26/EC)
  - Power according to ISO 8528 and ISO 3046
  - Ambient reference conditions 1000mbar, 25°C, 30% relative humidity ISO 3046
- Information based on standard specification equipment unless otherwise stated.